



## SECURITY LABELS

### Technical data sheet

#### FACE MATERIAL:

- Description** Imprintable matt silver polyester film, with a special absorbent surface coating, void printed.
- Use** Once applied to the substrates on removal, an irreversible “void” footprint message – formerly invisible to the eye – will detach itself from the face film. Labels which have been removed cannot be reapplied since repositioning will leave a visible proof that tampering has taken place.

TECHNICAL DATA	Weight	Caliper
	g/m2	Microns
	76	60

#### ADHESIVE:

- Description** A permanent, acrylic based adhesive
- Performances** It's perfectly suitable for uses that need a good resistance to UV, drippings or solvents. Good general adhesion performance on a wide variety of substrates.
- Shelf life** 2 years stored at 22°C and 50% RH

TECHNICAL DATA	Initial Tack	Application Temperature (min)	Service Temperature (min)	Service Temperature (max)
	N/mm	°C	°C	°C
	11	5	-40	+90

#### BACKING PAPER:

- Description** A one side coated, bleached kraft paper

TECHNICAL DATA	Weight	Caliper
	g/m2	Microns
	100	108

Our recommendations are based on our experience and up-to date knowledge. As the products are used outside our control, we cannot take the responsibility for any damage which could be caused when using the product. This technical information sheet replaces all ealier ones. All information could be changed without notice.