



## PLANETLUX FOR RINGS

### Technical data sheet

#### FACE MATERIAL:

- Description** White label paper, semi-gloss coated on one side
- Use** The material offers an excellent quality of the imprint with all traditional printing methods. The material is suited for high-quality labels with multi-colour imprint as well as thermo transfer printing.

TECHNICAL DATA	Weight	Caliper	Opacity
	g/m2	Microns	%
	80	68	88

#### ADHESIVE:

- Description** A permanent, acrylic based adhesive
- Performances** It's a universally applicable permanent adhesive. Its wide range of applications include price marking, computer labels and high quality industrial labels. It's resistant to light, heat and ageing.
- Shelf life** 2 year at a temperature 20-25 °C and 45/50 RH.

TECHNICAL DATA	Tack	Application Temperature (min)	Service Temperature (min)	Service Temperature (max)
		°C	°C	°C
	High	0	-30	+80

#### BACKING PAPER:

- Description** Honey, supercalendered glassine.
- Application** It's perfectly suited for assignment in labelling machines equipped with optical or mechanical scanners.

TECHNICAL DATA	Weight	Caliper	Transparency
	g/m2	Microns	%
	59	52	54

Our recommendations are based on our experience and up-to date knowledge. As the products are used outside our control, we cannot take the responsibility for any damage which could be caused when using the product. This technical information sheet replaces all ealier ones. All information could be changed without notice.

