

COLOURED LABELS (Red, Yellow, Green, Blue) Technical data sheet

FACE MATERIAL:

Description Coated woodfree paper with a matt colour finish

Application: The facestock's surface structure provides excellent toner bonding and print resolution.

Uses: Ideal for label applications using variable information such as address, instruction and inventory labels,

labels for office use many other applications.

| TECHNICAL | Grammage | Caliper |
|-----------|----------|----------|
| DATA | g/M2 | Micron μ |
| | 78 | 80 |

ADHESIVE:

Description A general purpose acrylic based adhesive.

Performances The favourable adhesive properties allow the products to be used on a wide range of flat curved

substrates, including packaging materials such as cardboard, plastic films and HDPE containers.

Shelf life 2 years, for the date of manufacture at $+20 \, \text{C}^{\circ}$ and 50% RH

| TECHNICAL DATA | Application Temperature (min) | Service Temperature (min) | Service Temperature (max) |
|-------------------|-------------------------------------|---------------------------|---------------------------|
| | °C | °C | °C |
| | 0 | -20 | +80 |

BACKING PAPER:

Description: One side coated bleached backing paper

Use: The product was tightly defined release characteristics to avoid predispensing during the printing or

coping process.

| | grammage | Caliper |
|-----------|----------|---------|
| TECHNICAL | g/m2 | Microns |
| DATA | 55 | 58 |

Our recommendations are based on our experience and up-to date knowledge. As the products are used outside our control, we cannot take the responsibility for any damage which could be caused when using the product. This technical information sheet replaces all ealier ones. All information could be changed without notice.