

JET GLOSS PAPER ON DEMAND Technical data sheet

FACE MATERIAL:

| Description | A white, high gloss, coated paper with a highly absorbent surface structure specifically designed for water-based inkjet printing. |
|-------------|---|
| Use | In labelling applications, when the advantages of digital printing is necessary: short runs, last minute changes, personalised layouts. |

| TECHNICAL | Weight | Caliper | |
|-----------|---------|-----------|--|
| DATA | 85 g/m2 | 58 Micron | |

ADHESIVE:

| Description | A general purpose permanent, acrylic based adhesive |
|--------------|---|
| Performances | The adhesive characterized by a high initial tack, excellent adhesion and good low temperature performance on a wide variety of substrates. |
| Shelf life | 2 years in +20° and RH 40-50% |

| TECHNICAL DATA | Tack (min) | Application Temperature (min) | Service Temperature (min) | Service Temperature (max) |
|-------------------|---------------|-------------------------------------|------------------------------|------------------------------|
| | N-FTM 9 | °C | °C | °C |
| | 15 N/25 | 0 | -20 | +80 |

BACKING PAPER:

Description

A white , supercalendered glassine paper

| | Caliper |
|-----------|---------|
| TECHNICAL | Microns |
| DATA | 55 |

Our recommendations are based on our experience and up-to date knowledge. As the products are used outside our control, we cannot take the responsibility for any damage which could be caused when using the product. This technical information sheet replaces all ealier ones. All information could be changed without notice.